



*** SAFETY DATA SHEET ***
Page 1 of 5

1. CHEMICAL PRODUCT and COMPANY IDENTIFICATION

Company Information:

The Gluefast Company, Inc.
3535 Route 66, Building #1
Neptune, NJ 07753 USA
Phone: 732.918.4600

Product Information:

Product Name / Number: 879 & 879H & 879S
Product Description: Water based adhesive

2. COMPOSITION / INFORMATION ON INGREDIENTS

This MSDS is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS). Unlisted ingredients are not "hazardous" per the OSHA standard and/or are not found on the WHMIS ingredient disclosure list.

<u>Chemical / CAS Number:</u>	<u>Percent</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Residual vinyl acetate	<.5%	10 ppm	10 ppm
Monomer (108-05-4)			
LD50: 2920 mg/kg (oral, rat) / LC50: 2828 ppm/4h (rat)			
Vapor Pressure, in mm Hg @ 20°C:92			
OSHA, ACGIH STEL: 20 ppm			

(See Section 16 for additional information.)

3. HAZARDOUS IDENTIFICATION

EMERGENCY OVERVIEW: Possible cancer hazard. Contains a material which may cause cancer.

POTENTIAL HEALTH EFFECTS:

EYES: Eye contact with liquid product may cause irritation.

SKIN: Prolonged or repeated contact with liquid product may cause irritation.

INHALATION: Exposure to vapors in poorly ventilated areas may cause irritation of the nose, throat and respiratory tract.

INGESTION: Not an anticipated route of exposure. Small amounts are not anticipated to be harmful.

CHRONIC: Overexposure to vinyl acetate is not expected to occur during normal handling and use of this product. Vinyl acetate has been shown to cause irritation and cancer in inhalation studies with laboratory animals. Test levels of 600 ppm caused an increase in tumors in the respiratory tract of the test animals. No tumors were observed in the animals exposed at 50 ppm or lower. There is no evidence that vinyl acetate has caused cancer in humans.

REGULATED CARCINOGEN STATUS: Vinyl acetate is listed as a potential carcinogen by IARC.

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: No known effects on other illnesses.



***** SAFETY DATA SHEET *****
Page 2 of 5

4. FIRST AID MEASURES

- IF IN EYE:** Flush immediately with water for 15 minutes. Consult a physician if irritation persists.
- IF ON SKIN:** Wash affected area with soap and water. Launder contaminated clothing before reuse.
- IF VAPORS INHALED:** Remove subject to fresh air.
- IF INGESTED:** If person can swallow, give one glass of water or milk. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

- FLASH POINT / METHOD:** Non-flammable
- UPPER EXPLOSIVE LIMIT / LOWER EXPLOSIVE LIMIT:** Not applicable
- AUTOIGNITION TEMPERATURE:** Not applicable
- APPROPRIATE EXTINGUISHERS:** Non-flammable in liquid state; use water spray, foam, dry chemical or carbon dioxide on dried product.
- SPECIAL FIRE FIGHTING PROCEDURES:** Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment.
- UNUSUAL FIRE and EXPLOSION HAZARDS:** There is the possibility of pressure and build-up in closed containers when heated. Water spray may be used to cool the containers.
- HAZARDOUS COMBUSTION PRODUCT:** Incomplete combustion can yield low molecular weight hydrocarbons, carbon monoxide.

6. ACCIDENTIAL RELEASE MEASURES

- SPILL or LEAK PROCEDURES:** Dike if necessary, contain spill with inert absorbent and transfer to containers for disposal. Keep spilled product out of sewers, watersheds or water systems.

7. HANDLING and STORAGE

HANDLING INFORMATION:

Wear appropriate protective equipment when working with this product.

STORAGE INFORMATION:

Avoid temperature extremes in storage.

*Consult the Technical Data Sheet for specific storage instructions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE PROTECTION: Wear safety glasses to reduce the potential for eye contact; chemical safety goggles are appropriate if splashing or dusting is likely. Have eye washes available where eye contact can occur.

SKIN PROTECTION: Prevent prolonged or repeated contact by using rubber gloves and appropriate protective clothing. Launder contaminated clothing before reuse.



***** SAFETY DATA SHEET *****
Page 3 of 5

RESPIRATORY PROTECTION: Not normally required. Use NIOSH/MSHA approved respirator if conditions warrant.

VENTILATION: General dilution ventilation.

9. PHYSICAL and CHEMICAL PROPERTIES

- Physical State: Liquid
- Color: White
- Odor: Mild. sweet
- Odor Threshold: Not established
- Weight per Gallon: 8.7 lbs
- Specific Gravity: 1.05
- % Solids by Weight: 52-54%
- pH: 4.8-5.5
- Boiling Range: Greater than 200°F (93°C)
- Freezing / Melting Point: Not established
- Vapor Pressure: Not established
- Vapor Density: Not established
- Evaporation Rate: Not established
- Water / Oil Partition Coefficient: Not established

10. STABILITY and REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: Not established

HAZARDOUS DECOMPOSITION: Not established

HAZARDOUS POLYMERIZATION: Will not occur

11. TOXICOLOGICAL INFORMATION

No Data Available

12. ECOLOGICAL INFORMATION

No Data Available

13. DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult the state, local or provincial authorities and your local waste vendor for more restrictive requirements.



*** SAFETY DATA SHEET ***
Page 4 of 5

14. TRANSPORTATION INFORMATION

UNITED STATES DEPARTMENT OF TRANSPORTATION (DOT)

DOT Proper Shipping Name: Not regulated

It is our opinion that the information provided here may be used to transport this product in compliance with Canadian Transportation of Dangerous Goods.

15. REGULATORY INFORMATION

FEDERAL:

Toxic Substances Control Act (TSCA)

Section 8 (b) – Inventory Status

This product is in compliance with the Toxic Substances Control Act's Inventory requirements.

Section 12 (b) – Export Notice Requirements

This product contains a chemical substance that is currently on the EPA's Section 12 (b) Export List. Within seven days of entering into a contract to export and certainly no later than the day of export, the agent of export must notify the EPA of their intent.

Contact The Gluefast Company TSCA Compliance Manager at 732.918.4614 for the identity of the Section 12 (b) chemical(s).

SARA TITLE III

Section 313

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Percent</u>
Vinyl acetate	108.05.4	<.5%

STATE REGULATIONS:

California Proposition 65: Proposition 65, The Safe Drinking Water and Toxic Enforcement Act of 1986:

This products contains chemical(s) known to the state of California to cause cancer (c) or reproductive (r) damage.

<0.0173% Formaldehyde (c) / 50.00.0

listed January 1, 1988

<0.0029% Toluene (r) / 108.88.3

listed January 1, 1991

WHMIS IDENTIFICATION / OTHER INTERNATIONAL REGULATIONS:

Health	1	Slightly Toxic
Fire	0	Minimal Hazard
Reactivity	0	Stable
Personal Protection	B	Safety Glasses, Gloves



GF#879 / GF 879H / GF 879S Adhesive

August 3, 2015

*** SAFETY DATA SHEET ***

Page 5 of 5

16. ADDITIONAL INFORMATION

In storage, monomer vapors will migrate from the emulsion and establish an equilibrium between the headspace in the storage container and the liquid emulsion. Levels in excess of acceptable exposures can accumulate in non-vented headspaces above the emulsion. All procedures appropriate for a confined space entry should be completed prior to performing any work in a bulk storage tank.

This product contains trace amounts (less than 0.1%) of formaldehyde. Formaldehyde has been identified as an animal carcinogen. Overexposure to formaldehyde should not occur with normal handling and use.

HMIS RATING:

HEALTH - 1

FLAMMABILITY – 0

REACTIVITY – 0

See Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION for personal protective equipment recommendations.

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to The gluefast Company, Inc. from its suppliers, and because The Gluefast Company, Inc. has no control over the conditions of handling and use, The Gluefast Company, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and The Gluefast Company, Inc. assumes no responsibility for the use or reliance thereon. It is the responsibility of the user of The Gluefast Company, Inc. products to comply with all applicable federal, state and local laws and regulations.

Revised Date: April 8, 2013