



Skid-Lock ® -Quickset-50

February 15, 2019

*****SAFETY DATA SHEET *****

Page 1 of 5

1. PRODUCT & COMPANY IDENTIFICATION

Product Name: Skid-Lock- Quickset-50
Product Type: Adhesive
Company Address:
The Gluefast Company, Inc.
3535 Route 66, Bldg. #1
Neptune, NJ 07753 USA
Phone 732-918-4600

2. HAZARDS IDENTIFICATION

Physical state: Liquid
Color: White
Odor: Slight

HEALTH: 1
FLAMMABILITY: 0
PHYSICAL HAZARD: 0
Personal Protection: See MSDS Section 8

CAUTION: ADHESIVE VAPORS MAY CAUSE SLIGHT IRRITATION OF THE EYES, SKIN OR RESPIRATORY SYSTEM

Relevant routes of exposure: Skin, Eyes, Ingestion

Potential Health Effects

Inhalation: Vapors may cause respiratory irritation.
Skin Contact: Liquid may cause skin irritation
Eye Contact: Liquid or vapors may cause eye irritation.
Ingestion: Small ingested amounts are not believed to produce adverse health effects. Contact physician.

Existing conditions aggravated by exposure:

None known. This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Trade secret Registry #13-5105484-501P	7732-18-5	

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. Get immediate medical attention.
Skin contact: Wash skin with soap and water.
Eye contact: Flush with copious quantities of water and seek medical advice.
Ingestion: Larger amounts (at least several ounces) should be removed from the stomach by induced vomiting or aspiration.



Skid-Lock ® -Quickset-50

February 15, 2019

*****SAFETY DATA SHEET *****

Page 2 of 5

5. FIRE FIGHTING MEASURES

Flash point:	Not applicable
Auto ignition temperature:	Unknown
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits – upper:	Not applicable
Extinguishing media:	For dry polymer use water, carbon dioxide (co2), or ABC dry chemical.
Special firefighting procedures:	When dried polymer burns, water (H2O), carbon dioxide (CO2), carbon monoxide (CO), and smoke are produced. Pyrolysis products may include some hazardous materials.
Unusual fire or explosion hazards:	No unusual fire or explosion hazards.
Hazardous combustion products:	Oxides of carbon

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not flush liquid material into public sewer or water system. Disposal of water/adhesive in accordance with federal, state and local regulations. Most states prohibit disposal of liquids in landfills.

Clean-up methods:

Contain spill. Recover as much as possible for reuse. Absorb remaining spill with an inert material. Place into closed container and store in a safe location to await disposal. Wash the spill area with soap and water.

Spilled material is very slippery. Use care to avoid falls. Dried film should be thoroughly cleaned. If spilled in an enclosed area, ventilate. Change contaminated clothing and launder before reuse. Wear proper personal protective clothing and equipment.

7. HANDLING AND STORAGE

Handling:

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling

Storage:

Store at room temperature. Rotate stock using oldest material first. KEEP FROM FREEZING. Shelf life is one year.



Skid-Lock ® -Quickset-50

February 15, 2019

*****SAFETY DATA SHEET *****

Page 3 of 5

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls:

Effective exhaust ventilation should always be provided to draw mists, fumes and vapors away from workers to prevent routine inhalation.

Respiratory protection:

None required except if product is being sprayed where a NIOSH approved mask is recommended.

Eyeface protection:

Safety goggles.

Skin protection:

Gloves recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	White
Odor:	Slight
Odor threshold:	Not available
Ph:	6-7
Vapor Pressure:	Water
Boiling Point/range:	212F
Freezing point/ range:	0 °C (32°F)
Vapor density:	Water
Flash Point:	Not Applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits – upper:	Not applicable
Autoignition temperature:	Unknown
Evaporation rate:	Water
Solubility in water:	Dispersible
Partition coefficient (n-octanol/water)	Not determined
VOC content:	0.4g/l or less



Skid-Lock ® -Quickset-50

February 15, 2019

*****SAFETY DATA SHEET *****

Page 4 of 5

10. STABILITY AND REACTIVITY

Stability	Stable
Hazardous reactions:	None
Hazardous decomposition products	Carbon monoxide, carbon dioxide & oxides of nitrogen.
Incompatible materials:	Materials that react with water & strong oxidizing agents.
Conditions to avoid:	Do not freeze

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTB Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
None	None	None	None
Hazardous components		Health Effects/ Target Organs	
None		None	

12. ECOLOGICAL INFORMATION

Ecological information: None available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Disposal of water/adhesive in accordance with federal, state and local regulations. Most states prohibit disposal of liquids in landfills.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: SLquik50GL, SLquik50PL, SLquik50DR
 Hazard class or division: None
 Identification number: None
 Packing group: Carton, 5-gallon pail, 55 gallon drum

Product is not regulated, non hazardous and not restricted for transport by air or water.



Skid-Lock ® -Quickset-50

February 15, 2019

*****SAFETY DATA SHEET *****

Page 5 of 5

INTERNATIONAL AIR TRANSPORTATION (ICAO/IATA)

Proper shipping name: SLquik50GL, SLquik50PL, SLquik50DR
Hazard class or division: None
Identification number: None
Packing group: Carton, 5-gallon pail, 55 gallon drum

Product is not regulated, non hazardous and not restricted for transport by air.

WATER TRANSPORTATION (IMO/MDG)

Proper shipping name: SLquik50GL, SLquik50PL, SLquik50DR
Hazard class or division: None
Identification number: None
Packing group: Carton, 5-gallon pail, 55 gallon drum

Product is not regulated, non hazardous and not restricted for transport by air or water.

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed on the TSCA inventory
TSCA 12 (b) Export Notification: None above reporting de minimus
CERCLA/SARA Section 302 EHS: None above reporting de minimus
CERCLA/SARA Section 311/312: None
CERCLA/SARA 313: None
FDA 21CFR175.105

California Proposition 65: N/A

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

WHMIS hazard class: Not controlled

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections:
New Safety Data Sheet format.

Revision Date: May 27, 2015

Page 5